

TOP MOUNT FILTERS-V SERIES



FEATURES

- Clamp Lock is designed to allow 360 degree rotation to simplify installation
- Top diffuser ensures even distribution of water over the sand bed
- Large pressure sand/water drain for rapid winterizing or servicing
- Materials used are dependable and are suitable for all-weather performance
- Easy-to-use Multiport Valve lets you select any of the valve/filter operation with a simple lever-action
- UV-resistance surface allows the work under direct sunlight

Maximum Working Pressure: 250kPa(36psi)
 Maximum Testing Pressure: 400kPa(58psi)
 Maximum Water Temperature: 43°C (109°F)

Maximum Filtration Velocity: 50m³/h/m²

TECHNICAL CHARACTERISTICS

Model No	Dimensions		Filter Area(m ²)	Valve Connection (inch)	Design Flow Rate(m ³)	Amount of Sand Required(kg)
	Width(mm)	Height(mm)				
V350	335	726	0.10	1 1/2"	4.02	18
V400	410	757	0.13	1 1/2"	6.30	33
V450	455	814	0.16	1 1/2"	7.98	50
V500	535	845	0.22	1 1/2"	11.52	85
V650	635	950	0.32	1 1/2"	16.20	140
V700	710	1020	0.40	1 1/2"	20.40	200
V800	800	1200	0.50	2"	24.60	280
V900	900	1300	0.64	2"	31.80	350
V1000	1000	1400	0.79	2"	39.00	650
V1100	1100	1480	0.98	2"	46.80	950
V1200	1200	1600	1.13	2"	51.60	1200
V1400	1400	1850	1.54	2"	63.00	2000