

Ultraviolet Water Sterilizer

AQUAPRO UV STANDARD FEATURES

- Heavy duty stainless steel pressure vessel
- Heavy duty quartz sleeve
- High output, hard glass UV lamps for maximum efficiency
- CE ballast with lamp failure indicator and warning buzzer
- Ceramic end cap of UV lamp
- 30000mic. watt sec/cm² at energy of 253.7nm wave length
- Working pressure 125PSI
- Low power consumption
- 9000 hours lamp life (approx. 1 year of use)
- 110/220V, 50HZ/60HZ
- Vertical or Horizontal installation
- UV light Monitor available



6-12GPM UV STERILIZER-HORIZONTAL TYPE STANDARD SPECIFICATION-UV6GPM-H

DIMENSION LxWxD (mm)	560X80X80
ELECTRICAL VOLTS	110/220V 50/60HZ
FLOW RATE	6GPM
IN/OUT PORT	1/2"
UV LAMP (PC)	1
QUARTZ SLEEVE (PC)	1
LAMP FAILURE DEVICE	YES
AMBIENT TEMPERATURE	2~40°C (36~104°F)
LAMP WATTS	20W
CHAMBER	SS304

AQUAPRO INDUSTRIAL CO., LTD

Head Office :

7F, No. 202, Sec. 5, Nanking E. Rd., Taipei, Taiwan,
R.O.C.

Tel : 886-2-27673018

Fax : 886-2-27663197

E-mail : aquapro.taiwan@msa.hinet.net

http : // www.aquapro.com.tw

Factory:

No. 388, Sec. 5, Yuan-Lu Rd.,
Pu-Hsin, Chang-Hua Hsien, Taiwan, R.O.C.

Tel: 886-4-829 5857

Fax: 886-4-829 5838

Ultraviolet Water Sterilizer



UV12GPM-HTM

STANDARD SPECIFICATION

DIMENSION LxWxD (mm)	900X170X89 (UV12GPM-H) 900X190X160 (UV12GPM-HTM)
ELECTRICAL VOLTS	110/220V 50/60HZ
FLOW RATE	12GPM
IN/OUT PORT	3/4"
UV LAMP (PC)	1
QUARTZ SLEEVE (PC)	1
LAMP FAILURE DEVICE	YES
AMBIENT TEMPERATURE	2~40°C (36~104°F)
LAMP WATTS	39W
CHAMBER	SS304
ACCUMULATED TIMER	UV12GPM-HT UV12GPM-HTM
UV LIGHT MONITOR	UV12GPM-HTM

AQUAPRO INDUSTRIAL CO., LTD

Head Office :

7F, No. 202, Sec. 5, Nanking E. Rd., Taipei, Taiwan,
R.O.C.

Tel : 886-2-27673018

Fax : 886-2-27663197

E-mail : aquapro.taiwan@msa.hinet.net

http : // www.aquapro.com.tw

Factory:

No. 388, Sec. 5, Yuan-Lu Rd.,
Pu-Hsin, Chang-Hua Hsien, Taiwan, R.O.C.

Tel: 886-4-829 5857

Fax: 886-4-829 5838

Ultraviolet Water Sterilizer

6-12GPM UV STERILIZER-VERTICAL TYPE

STANDARD SPECIFICATION



	UV6GPM-V	UV12GPM-V
DIMENSION LxWxD (mm)	650X80X140	900X89X170
ELECTRICAL VOLTS	110/220V, 50/60HZ	110/220V, 50/60HZ
FLOW RATE	6GPM	12GPM
IN/OUT PORT	1/2"	3/4"
UV LAMP (PC)	1	1
QUARTZ SLEEVE (PC)	1	1
LAMP FAILURE DEVICE	YES	YES
AMBIENT TEMPERATURE	2~40°C (36~104°F)	2~40°C (36~104°F)
LAMP WATTS	20W	39W
CHAMBER	SS304	SS304
ACCUMULATED TIMER	YES	YES

AQUAPRO INDUSTRIAL CO., LTD

Head Office :

7F, No. 202, Sec. 5, Nanking E. Rd., Taipei, Taiwan, R.O.C.

Tel : 886-2-27673018

Fax : 886-2-27663197

E-mail : aquapro.taiwan@msa.hinet.net

http : // www.aquapro.com.tw

Factory:

No. 388, Sec. 5, Yuan-Lu Rd.,

Pu-Hsin, Chang-Hua Hsien, Taiwan, R.O.C.

Tel: 886-4-829 5857

Fax: 886-4-829 5838